

# CuZn objímky a konektory s izoláciou

## WI...BPVC - plochý konektor

**Materiál:** CuZn  
**Povrchová úprava:** počinované  
**Izolácia:** PVC  
**Pracovná teplota:** od -5°C do +60°C



Tovar  
na objednávku

TYP	Rozmer (mm)	Prierez (mm <sup>2</sup> )	Rozmery (mm)			Balenie (ks)	Číslo produktu
			L <sub>2</sub>	L <sub>1</sub>	d		
WI 2,8-1/0,5BPVC	2,5x0,5	0,5-1	7,2	22,0	1,9	100	4.0228313
WI 2,8-1/0,8BPVC	2,8x0,8	0,5-1	7,2	22,0	1,9	100	4.0228312
WI 4,8-1/0,5BPVC	4,8x0,5	0,5-1	7,2	22,0	1,9	100	4.0228323
WI 4,8-1/0,8BPVC	4,8x0,8	0,5-1	7,2	22,0	1,9	100	4.0228322
WI 6,3-1/0,8BPVC	6,3x0,8	0,5-1	8,0	22,0	1,9	100	4.0228331
WI 4,8-2,5/0,5BPVC	4,8x0,5	1,5-2,5	7,2	22,5	2,5	100	4.0228346
WI 4,8-2,5/0,8BPVC	4,8x0,8	1,5-2,5	7,2	22,5	2,5	100	4.0228347
WI 6,3-2,5/0,8BPVC	6,3x0,8	1,5-2,5	8,0	22,5	2,5	100	4.0228348
WI 6,3-6/0,8BPVC	6,3x0,8	4-6	8,0	22,5	3,7	100	4.0228351

