

OCHRANA KÁBLOV

HV - priechodky z PA

Materiál: PA 6,6; bezhalogénové prevedenie
Pracovná teplota: od -40°C do +85°C
Farba: čierna BK; biela WT
Trieda horľavosti: UL 94 V2



TYP	Rozmery (mm)				Balenie (ks)	Číslo produktu
	A	B	C	L		
HV-3/BK	6,4	3,2	8,0	8,0	100	3.0020000
HV-5/BK	7,6	4,8	12,0	8,0	100	3.0020100
HV-6/BK	9,5	6,3	12,0	10,3	100	3.0020300
HV-8/BK	11,1	8,0	15,0	10,3	100	3.0020380
HV-9/BK	12,7	8,2	14,5	10,3	100	3.0020430
HV-12/BK	15,9	12,2	18,6	10,3	100	3.0020530
HV-15/BK	19,1	14,3	21,5	10,3	100	3.0020660
HV-16/BK	19,6	16,0	24,0	11,5	100	3.0020730
HV-19/BK	22,0	17,3	23,8	11,5	100	3.0020830
HV-21/BK	25,1	19,1	28,0	11,5	100	3.0020920
HV-24/BK	29,7	24,1	32,5	11,5	100	3.0021000
HV-29/BK	38,1	29,0	41,2	11,5	100	3.0021260
HV-6/WT	9,5	6,3	12,0	10,3	100	3.0020305
HV-8/WT	11,1	8,0	15,0	10,3	100	3.0020385
HV-12/WT	15,9	12,2	18,6	10,3	100	3.0020535
HV-16/WT	19,6	16,0	24,0	11,5	100	3.0021735

