

OCHRANA KÁBLOV

OD - vývodky PG a M so špirálou

Materiál: telo: PA6; bezhalogénové prevedenie
Pracovná teplota: od -20°C do +80°C
Farba: sivá (RAL 7035); čierna BK (RAL 90025)
Stupeň ochrany: IP68
Trieda horľavosti: UL94V2
Norma: EN 62444, typ A



Tovar
na objednávku

TYP	Závit PG a M	Vonkajší priemer kábla (mm)	Rozmery (mm)		Rozmer kľúča A (mm)	Balenie (ks)	Číslo produktu
			L	E			
OD-7P	P7	3,0 - 6,5	49	8	15	10	3.0032380
OD-9P	P9	4,0 - 8,0	59	8	19	10	3.0032410
OD-11P	P11	5,0 - 10,0	71	8	22	10	3.0032440
OD-13P	P13,5	6,0 - 12,0	81	9	24	10	3.0032470
OD-16P	P16	10,0 - 14,0	93	10	27	10	3.0032480
OD-21P	P21	13,0 - 18,0	111	11	33	10	3.0032500
OD-7P/BK	P7	3,0 - 6,5	49	8	15	10	3.0032381
OD-9P/BK	P9	4,0 - 8,0	59	8	19	10	3.0032411
OD-11P/BK	P11	5,0 - 10,0	71	8	22	10	3.0032441
OD-13P/BK	P13,5	6,0 - 12,0	81	9	24	10	3.0032471
OD-16P/BK	P16	10,0 - 14,0	93	10	27	10	3.0032481
OD-21P/BK	P21	13,0 - 18,0	111	11	33	10	3.0032501
OD-12PM	M12x1,5	3,0 - 6,5	49	8	15	10	3.0032900
OD-16PM	M16x1,5	5,0 - 10,0	59	10	22	10	3.0032910
OD-20PM	M20x1,5	6,0 - 12,0	81	10	24	10	3.0032920
OD-20PM2	M20x1,5	10,0 - 14,0	93	10	27	10	3.0032930
OD-25PM	M25x1,5	13,0 - 18,0	111	10	33	10	3.0032940
OD-12PM/BK	M12x1,5	3,0 - 6,5	49	8	15	10	3.0032901
OD-16PM/BK	M16x1,5	5,0 - 10,0	59	10	22	10	3.0032911
OD-20PM/BK	M20x1,5	6,0 - 12,0	81	10	24	10	3.0032921
OD-20PM2/BK	M20x1,5	10,0 - 14,0	93	10	27	10	3.0032931
OD-25PM/BK	M25x1,5	13,0 - 18,0	111	10	33	10	3.0032941

Vývodka sa dodáva bez matice (N) a tesnenia (UUPE).

