

OCHRANA KÁBLOV

PDE - gumové priechodky PG

Materiál: guma EPDM; bezhalogénové prevedenie
Pracovná teplota: od -40°C do +110°C
Farba: sivá (RAL 7001); biela WT (RAL 9001); čierna BK (RAL 9005)
Stupeň ochrany: IP67
Trieda horľavosti: UL 94 HB
Norma: EN 60529



Tovar
na objednávku

TYP	Rozmery (mm)					Vonkajší priemer kábla (mm)	Balenie (ks)	Číslo produktu
	Da	H	H1	A	B			
PDE-7	20	12,6	5,4	13	0,5 - 2	3 - 5	50	3.0401015
PDE-9	21	17,8	10,3	16	1 - 4	5 - 7	50	3.0401025
PDE-11	24	19,8	12,7	19	1 - 4	7 - 10	50	3.0401035
PDE-16	28	21,8	14,7	23	1 - 4	10 - 14	50	3.0401045
PDE-21	35	24,6	17,6	29	1 - 4	14 - 20	25	3.0401055
PDE-29	46	28,5	20,0	38	1 - 4	20 - 26	25	3.0401065
PDE-36	58	34,9	23,9	48	1 - 4	26 - 35	10	3.0401075
PDE-7/WT	20	12,6	5,4	13	0,5 - 2	3 - 5	50	3.0401016
PDE-9/WT	21	17,8	10,3	16	1 - 4	5 - 7	50	3.0401026
PDE-11/WT	24	19,8	12,7	19	1 - 4	7 - 10	50	3.0401036
PDE-16/WT	28	21,8	14,7	23	1 - 4	10 - 14	50	3.0401046
PDE-21/WT	35	24,6	17,6	29	1 - 4	14 - 20	25	3.0401056
PDE-29/WT	46	28,5	20,0	38	1 - 4	20 - 26	25	3.0401066
PDE-36/WT	58	34,9	23,9	48	1 - 4	26 - 35	10	3.0401076
PDE-7/BK	20	12,6	5,4	13	0,5 - 2	3 - 5	50	3.0401017
PDE-9/BK	21	17,8	10,3	16	1 - 4	5 - 7	50	3.0401027
PDE-11/BK	24	19,8	12,7	19	1 - 4	7 - 10	50	3.0401037
PDE-16/BK	28	21,8	14,7	23	1 - 4	10 - 14	50	3.0401047
PDE-21/BK	35	24,6	17,6	29	1 - 4	14 - 20	25	3.0401057
PDE-29/BK	46	28,5	20,0	38	1 - 4	20 - 26	25	3.0401067
PDE-36/BK	58	34,9	23,9	48	1 - 4	26 - 35	10	3.0401077

