

OCHRANA KÁBLOV

BDE - gumové vývodky

Materiál: guma SBR+NR; bezhalogénové prevedenie
Pracovná teplota: od -30°C do +85°C
Farba: biela WT (RAL 9001); čierna BK (RAL 9005)
Stupeň ochrany: IP30 min.



Tovar
na objednávku

TYP	Rozmery (mm)					Vonkajší priemer kábla (mm)	Balenie (ks)	Číslo produktu
	H	D	d	L	A			
BDE-11/BK	4	24	7,0	30	16,5	6 - 8	100	3.0411011
BDE-13/BK	6	31	8,0	23	21	9 - 12	100	3.0411021
BDE-16/BK	6	34	10,5	23	23	11 - 15	100	3.0411031
BDE-21/BK	6	42	13,5	25	29	14 - 18	100	3.0411041
BDE-29/BK	7	50	17,0	30	38	18 - 25	50	3.0411051
BDE-36/BK	8	62	22,0	34	48	24 - 34	20	3.0411061
BDE-42/BK	8	63	31,0	39	55	31 - 44	10	3.0411071
BDE-48/BK	8	72	41,0	45	65	40 - 54	10	3.0411081
BDE-54/BK	8	85	51,0	50	78	52 - 66	10	3.0411091
BDE-67/BK	8	97	63,0	63	90	65 - 78	10	3.0411101
BDE-11/WT	4	24	7,0	30	16,5	6 - 8	100	3.0411010
BDE-13/WT	6	31	8,0	23	21	9 - 12	100	3.0411020
BDE-16/WT	6	34	10,5	23	23	11 - 15	100	3.0411030
BDE-21/WT	6	42	13,5	25	29	14 - 18	100	3.0411040
BDE-29/WT	7	50	17,0	30	38	18 - 25	50	3.0411050
BDE-36/WT	8	62	22,0	34	48	24 - 34	20	3.0411060
BDE-42/WT	8	63	31,0	39	55	31 - 44	10	3.0411070
BDE-48/WT	8	72	41,0	45	65	40 - 54	10	3.0411080
BDE-54/WT	8	85	51,0	50	78	52 - 66	10	3.0411090
BDE-67/WT	8	97	63,0	63	90	65 - 78	10	3.0411100

