

WOT - ochranná hadica oceľová, poplastovaná

Materiál: pozinkovaná oceľ + PVC
Pracovná teplota: od -5°C do +80°C
Odolnosť voči korózií: 3 (stredná) EN 61386-1
Odolnosť na tlak: 4 (1250 N)
Stupeň ochrany: IP66
Norma: EN 61386-1, EN 61386-23
Farba: sivá; čierna BK



TYP	Rozmery (mm)		Polomer ohybu min. (mm)	Balenie (m)	Číslo produktu
	d	D			
WOT-7/10	9,4	12,5	32	10	3.0350100
WOT-9/10	11,0	15,2	40	10	3.0350110
WOT-11/10	14,0	18,6	45	10	3.0350120
WOT-13/10	15,0	20,4	52	10	3.0350130
WOT-16/10	17,0	22,5	58	10	3.0350140
WOT-21/10	22,0	28,3	72	10	3.0350150
WOT-29/10	30,0	37,0	96	10	3.0350160
WOT-36/10	39,0	47,0	118	10	3.0350170
WOT-48/10	50,0	60,0	140	10	3.0350180
WOT-63/10	63,0	72,0	200	10	3.0350182
WOT-75/10	78,0	88,0	225	10	3.0350184
WOT-100/10	102,0	112,0	275	10	3.0350186
WOT-7/10/BK	9,4	12,5	32	10	3.0350101
WOT-9/10/BK	11,0	15,2	40	10	3.0350111
WOT-11/10/BK	14,0	18,6	45	10	3.0350121
WOT-13/10/BK	15,0	20,4	52	10	3.0350131
WOT-16/10/BK	17,0	22,5	58	10	3.0350141
WOT-21/10/BK	22,0	28,3	72	10	3.0350151
WOT-29/10/BK	30,0	37,0	96	10	3.0350161
WOT-36/10/BK	39,0	47,0	118	10	3.0350171
WOT-48/10/BK	50,0	60,0	140	10	3.0350181
WOT-63/10/BK	63,0	72,0	200	10	3.0350183
WOT-75/10/BK	78,0	88,0	225	10	3.0350185
WOT-100/10/BK	102,0	112,0	275	10	3.0350187

