

OCHRANA KÁBLOV

MWO, MWO...M - vývodky pre hadice WO, WOT

Materiál: poniklovaná CuZn, vložka PE; bezhalogénové prevedenie
Pracovná teplota: od -30°C do +80°C
Stupeň ochrany: IP66



Tovar
na objednávku

TYP	Závit PG / M	Pre hadice		Rozmery (mm)			Rozmer kľúča		Balenie (ks)	Číslo produktu
				C	L	E	A (mm)	B (mm)		
MWO-7	P7	WO-7	WOT-7	7,5	10,0	6,0	19	17	10	3.0350400
MWO-9	P9	WO-9	WOT-9	9,2	12,5	6,0	22	20	10	3.0350410
MWO-11	P11	WO-11	WOT-11	11,9	13,0	7,0	26	24	10	3.0350420
MWO-13	P13,5	WO-13	WOT-13	13,6	13,0	7,0	28	26	10	3.0350430
MWO-16	P16	WO-16	WOT-16	15,3	14,0	8,0	30	28	10	3.0350440
MWO-21	P21	WO-21	WOT-21	20,2	16,5	8,0	36	34	10	3.0350450
MWO-29	P29	WO-29	WOT-29	26,7	13,5	10,0	47	45	10	3.0350460
MWO-36	P36	WO-36	WOT-36	34,6	26,5	11,0	60	56	10	3.0350470
MWO-48	P48	WO-48	WOT-48	45,3	33,0	15,0	74	70	10	3.0350480
MWO-12M/7	M12x1,5	WO-7	WOT-7	7,5	10,2	6,0	19	17	10	3.0350401
MWO-16M/9	M16x1,5	WO-9	WOT-9	9,2	12,5	6,0	22	20	10	3.0350411
MWO-20M/11	M20x1,5	WO-11	WOT-11	11,9	13,0	7,0	26	24	10	3.0350421
MWO-20M/13	M20x1,5	WO-13	WOT-13	13,6	13,2	7,0	28	26	10	3.0350431
MWO-25M/16	M25x1,5	WO-16	WOT-16	15,3	14,0	8,0	30	28	10	3.0350441
MWO-25M/21	M25x1,5	WO-21	WOT-21	20,2	16,5	6,5	36	34	10	3.0350451
MWO-32M/21	M32x1,5	WO-21	WOT-21	20,2	16,5	8,0	36	36	10	3.0350462
MWO-32M/29	M32x1,5	WO-29	WOT-29	26,7	19,5	6,5	47	45	10	3.0350471
MWO-40M/29	M40x1,5	WO-29	WOT-29	26,7	19,5	10,0	47	45	10	3.0350482
MWO-40M/36	M40x1,5	WO-36	WOT-36	34,6	26,0	8,5	60	56	10	3.0350485
MWO-50M/36	M50x1,5	WO-36	WOT-36	34,6	26,0	11,0	60	58	10	3.0350486
MWO-63M/48	M63x1,5	WO-48	WOT-48	45,3	32,5	15,0	74	70	10	3.0350487

Vývodka sa dodáva bez matice (MDN, MDN...M) a bez tesnenia (UUPE, UUPE...M).

