

FD, FD...BK - vývodky PG pre hadice WTE...

Materiál: PA 6.6, bezhalogénové prevedenie
Pracovná teplota: od -40°C do +120°C
Stupeň ochrany: IP54
Farba: sivá; čierna (BK)



Tovar
na objednávku

TYP	Rozmery (mm)			Rozmer kľúča A (mm)	Balenie (ks)	Číslo produktu
	D	E	L			
FD-7	18,2	10	29,0	13	10	3.0351000
FD-9	21,3	10	29,5	18	10	3.0351010
FD-11	24,0	10	30,5	19	10	3.0351020
FD-13	26,7	10	30,0	22	10	3.0351030
FD-16	29,7	10	30,5	26	10	3.0351040
FD-21	38,0	11	36,7	32	10	3.0351050
FD-29	45,2	12	41,8	40	10	3.0351060
FD-36	54,0	12	45,4	50	1	3.0351070
FD-48	65,3	12	45,7	64	1	3.0351080
FD-7BK	18,2	10	29,0	13	10	3.0351001
FD-9BK	21,3	10	29,5	18	10	3.0351011
FD-11BK	24,0	10	30,5	19	10	3.0351021
FD-13BK	26,7	10	30,0	22	10	3.0351031
FD-16BK	29,7	10	30,5	26	10	3.0351040
FD-21BK	38,0	11	36,7	32	10	3.0351051
FD-29BK	45,2	12	41,8	40	10	3.0351061
FD-36BK	54,0	12	45,4	50	1	3.0351071
FD-48BK	65,3	12	45,7	64	1	3.0351081

Vývodka sa dodáva bez matice (N.../H) a bez tesnenia (UUPE).

Vývodky sú určené pre hadice WTE, WTE...L, WTE...R, WTE...W.

