

FKD, FKD...BK - vývodky PG pre hadice WTE...

Materiál: PA 6, bezhalogénové prevedenie
Pracovná teplota: od -40°C do +120°C
Stupeň ochrany: IP54
Farba: sivá; čierna (BK)



Tovar na objednávku

TYP	Rozmery (mm)			Rozmer kľúča A (mm)	Balenie (ks)	Číslo produktu
	H	L	E			
FKD-7	46,5	20,5	10	13	10	3.0351100
FKD-9	53,0	25,0	10	18	10	3.0351110
FKD-11	54,5	25,5	10	19	10	3.0351120
FKD-13	58,5	29,5	10	22	10	3.0351130
FKD-16	59,0	31,5	11	26	10	3.0351140
FKD-21	74,0	38,5	11	32	10	3.0351150
FKD-29	89,0	47,0	12	40	10	3.0351160
FKD-36	107,0	58,0	12	50	1	3.0351170
FKD-48	121,0	72,0	13	64	1	3.0351180
FKD-7BK	46,5	20,5	10	13	10	3.0351101
FKD-9BK	53,0	25,0	10	18	10	3.0351111
FKD-11BK	54,5	25,5	10	19	10	3.0351121
FKD-13BK	58,5	29,5	10	22	10	3.0351131
FKD-16BK	59,0	31,5	11	26	10	3.0351141
FKD-21BK	74,0	38,5	11	32	10	3.0351151
FKD-29BK	89,0	47,0	12	40	10	3.0351161
FKD-36BK	107,0	58,0	12	50	1	3.0351171
FKD-48BK	121,0	72,0	13	64	1	3.0351181

Vývodka sa dodáva bez matice (N.../H) a bez tesnenia (UUPE).

Vývodky sú určené pre hadice WTE, WTE...L, WTE...R, WTE...W.

