

OCHRANA KÁBLOV

WPD - vývodky PG pre hadice WTG

Materiál: PVC
Pracovná teplota: od -20°C do +90°C
Montážna teplota: od -5°C do +30°C
Stupeň ochrany: IP66
Farba: čierna
Trieda horľavosti: UL 94 V0
Norma: DIN 40430



Tovar
na objednávku

TYP	Rozmery (mm)				Rozmer kľúča A (mm)	Rozmer kľúča B (mm)	Balenie (ks)	Číslo produktu
	L	C	E	e				
WPD-7/7	34	8,0	10,0	2,5	23	22	10	3.0350700
WPD-9/9	15	10,0	10,0	2,5	25	24	10	3.0350710
WPD-11/9	16	10,0	10,0	2,5	25	24	10	3.0350720
WPD-13/13	25	13,0	12,5	2,5	30	29	10	3.0350730
WPD-16/16	29	16,0	12,5	3,0	33	33	10	3.0350740
WPD-21/21	23	20,0	12,5	2,5	38	36	10	3.0350750
WPD-29/29	62	25,0	15,0	4,0	45	43	10	3.0350760
WPD-36/36	55	38,2	17,5	-	60	58	1	3.0350770
WPD-48/48	55	47,8	19,5	-	70	70	1	3.0350780

Vývodka sa dodáva bez matice (N.../H BK) a bez tesnenia (UUPE).

