

Krytky na CuZn objímky

ONZ - krytka objímiek, priama

Materiál: PA
Pracovná teplota: od -30°C do +70°C



| TYP | Pre typ koncovky | Rozmer (mm) | Prierez (mm ²) | Farba | Rozmery (mm) | | | Balenie (ks) | Číslo produktu |
|-------------|------------------|-------------|----------------------------|---------------|--------------|----------------|----------------|--------------|----------------|
| | | | | | L | L ₁ | L ₂ | | |
| ONZ 2,8/1 | N; NR | 2,8 | 0,5-1 | transparentná | 18 | - | - | 100 | 4.0228520 |
| ONZ 4,8/2,5 | N; NR; NZ | 4,8 | 1-2,5 | transparentná | 23,0 | 6,3x2,8 | 4,5x2,5 | 100 | 4.0228521 |
| ONZ 6,3/6 | N; NR; NZ | 6,3 | 1-6 | transparentná | 26,5 | 7,8x3,2 | 6,0x1,5 | 100 | 4.0228522 |
| ONZ 6,3/6BK | N; NR; NZ | 6,3 | 1-6 | čierna | 26,5 | 7,8x3,2 | 6,0x1,5 | 100 | 4.0228523 |
| ONZ 6,3/6WT | N; NR; NZ | 6,3 | 1-6 | biela | 26,5 | 7,8x3,2 | 6,0x1,5 | 100 | 4.0228524 |
| ONZ 6,3/6RD | N; NR; NZ | 6,3 | 1-6 | červená | 26,5 | 7,8x3,2 | 6,0x1,5 | 100 | 4.0228525 |
| ONZ 6,3/6BL | N; NR; NZ | 6,3 | 1-6 | modrá | 26,5 | 7,8x3,2 | 6,0x1,5 | 100 | 4.0228526 |
| ONZ 6,3/6GR | N; NR; NZ | 6,3 | 1-6 | zelená | 26,5 | 7,8x3,2 | 6,0x1,5 | 100 | 4.0228527 |
| ONZ 6,3/6YL | N; NR; NZ | 6,3 | 1-6 | žltá | 26,5 | 7,8x3,2 | 6,0x1,5 | 100 | 4.0228528 |
| ONZ 6,3/6VL | N; NR; NZ | 6,3 | 1-6 | fialová | 26,5 | 7,8x3,2 | 6,0x1,5 | 100 | 4.0228529 |
| ONZ 6,3/6BR | N; NR; NZ | 6,3 | 1-6 | hnedá | 26,5 | 7,8x3,2 | 6,0x1,5 | 100 | 4.0228530 |

