

Lisovacie náradie



K05C/6KT/6-50/Cu-RMC



K06C/6KT/6-120/Cu-RMC



K06/6KT/16-120/Al-c



K06F/6KT/25-150/Al-c



TYP	Prierez (mm ²)	Typ koncovky	Dĺžka (mm)	Hmotnosť (kg)	Číslo produktu
K05C/6KT/6-50/Cu-RMC	6-50	Cu RMC	390	1,4	5.0232260
K06C/6KT/6-120/Cu-RMC	6-120		650	4,5	5.0232265
K06/6KT/16-120/Al-c	16-120	Al-c	650	4,5	5.0232120
K06F/6KT/25-150/Al-c	25-150		650	4,5	5.0232125

Cu standard	= KWR, KOR, KM, KORo, K90R, K90M, K45R, K45M, KOR2x, KM2x, KL, ZM, KLS, KT, KX
Cu EKO	= KREo, LE
Cu RMC	= CKOR, CKL
Cu DIN	= KDR, KDM, K90D, K45D, KPD, KDR2x, KDM2x, KRM, KLD, LMP, LMW, LMWP, BMV, BMK
Al-c	= 2Kam, 2ZA
Al-g	= KA, KLA
Al DIN	= KRA, KRAC, KRAS, KRASC, KDA, KDAC, KDA2x, LA, LAS, KLAN, BAW, BAK, LAP, LAWP, LAW, TMA, KCA, LMAN, LMANW, BMAN
Al-Cu	= TMA, KCA, LMAN, LMANW, BMAN
sm; se	= pre formátovanie sektorových žíl na kruhové
neizolované	= KO, KW, KI, KL
izolované	= KOI, KWI, KII, KLI
dutinky	= H, HI
dutinky dvojité	= HI2x
spojky vzduš. ved.	= ZLA