

OCHRANA KÁBLOV

WSN - viazacia špirála

Materiál: PE bezhalogénový
Pracovná teplota: od -30°C do +70°C
Farba: transp. a čierna (UL94HB), biela (UL94V2)



TYP		Rozmery (mm)			Priemer zväzku (mm)	Balenie (m)	Číslo produktu
		D	T	S			
WSN-3	transparentná	3	0,75	5	3 - 10	10	3.0SP0002
WSN-6		6	1,00	7	6 - 50	10	3.0SP0004
WSN-8		8	1,00	11	8 - 60	10	3.0SP0006
WSN-10		10	1,00	12	10 - 60	10	3.0SP0008
WSN-12		12	1,50	14	12 - 65	10	3.0SP0010
WSN-15		15	1,50	15	15 - 70	10	3.0SP0012
WSN-19		19	2,00	18	19 - 100	10	3.0SP0015
WSN-24		24	2,00	20	24 - 130	10	3.0SP0020
WSN-3S	čierna	3	0,75	5	3 - 10	10	3.0SPA002
WSN-6S		6	1,00	7	6 - 50	10	3.0SPA004
WSN-8S		8	1,00	11	8 - 60	10	3.0SPA006
WSN-10S		10	1,00	12	10 - 60	10	3.0SPA008
WSN-12S		12	1,50	14	12 - 65	10	3.0SPA010
WSN-15S		15	1,50	15	15 - 70	10	3.0SPA012
WSN-19S		19	2,00	18	19 - 100	10	3.0SPA015
WSN-24S		24	2,00	20	24 - 130	10	3.0SPA020
WSN-3V2	biela	3	0,75	5	3 - 10	10	3.0SPV002
WSN-6V2		6	1,00	7	6 - 50	10	3.0SPV004
WSN-8V2		8	1,00	11	8 - 60	10	3.0SPV006
WSN-10V2		10	1,00	12	10 - 60	10	3.0SPV008
WSN-12V2		12	1,50	14	12 - 65	10	3.0SPV010
WSN-15V2		15	1,50	15	15 - 70	10	3.0SPV012
WSN-19V2		19	2,00	18	19 - 100	10	3.0SPV015
WSN-24V2		24	2,00	20	24 - 130	10	3.0SPV020

