

DP-EN - vývodky M

Materiál: telo: PA6
Pracovná teplota: od -30°C do +80°C
Farba: sivá (RAL 7035); čierna BK (RAL 90025)
Stupeň ochrany: IP68
Trieda horľavosti: UL94V2
Norma: EN 62444, typ A



TYP	Závit M	Vonkajší priemer kábla (mm)	Rozmery (mm)		Rozmer kľúča (mm)			Balenie (ks)	Číslo produktu
			L	E	A	B	C		
DP-EN-12HM	M12x1,5	3,0 - 6,5	22	8	16	16	18	10	3.0032610
DP-EN-16HM	M16x1,5	4,0 - 8,0	26	8	19	19	22	10	3.0032640
DP-EN-20HM	M20x1,5	7,0 - 12,0	28	9	24	24	26	10	3.0032670
DP-EN-25HM	M25x1,5	11,0 - 18,0	36	10	32	32	33	10	3.0032700
DP-EN-32HM	M32x1,5	16,0 - 21,0	40	11	35	36	39	10	3.0032760
DP-EN-40HM	M40x1,5	20,0 - 32,0	48	18	53	51	50	10	3.0032790
DP-EN-50HM	M50x1,5	30,0 - 38,0	49	18	61	60	60	1	3.0032840
DP-EN-63HM	M63x1,5	36,0 - 44,0	50	18	66	68	74	1	3.0032850
DP-EN-63-2HM	M63x1,5	42,0 - 50,0	58	26	76	76	76	1	3.0032855
DP-EN-12HM/BK	M12x1,5	3,0 - 6,5	22	8	16	16	18	10	3.0032611
DP-EN-16HM/BK	M16x1,5	4,0 - 8,0	26	8	19	19	22	10	3.0032641
DP-EN-20HM/BK	M20x1,5	7,0 - 12,0	28	9	24	24	26	10	3.0032671
DP-EN-25HM/BK	M25x1,5	11,0 - 18,0	36	10	32	32	33	10	3.0032701
DP-EN-32HM/BK	M32x1,5	16,0 - 21,0	40	11	35	36	39	10	3.0032761
DP-EN-40HM/BK	M40x1,5	20,0 - 32,0	48	18	53	51	50	10	3.0032791
DP-EN-50HM/BK	M50x1,5	30,0 - 38,0	49	18	61	60	60	1	3.0032841
DP-EN-63HM/BK	M63x1,5	36,0 - 44,0	50	18	66	68	74	1	3.0032851
DP-EN-63-2HM/BK	M63x1,5	42,0 - 50,0	58	26	76	76	76	1	3.0032856

Vývodka sa dodáva s maticou (N) a tesneným (UUPE).

