

# OCHRANA KÁBLOV

## KDD - rohové výstupy PG a M s vývodkou

**Materiál:** telo: PA6; tesnenie: NBR; bezhalog. prevedenie  
**Pracovná teplota:** od -20°C do +80°C  
**Farba:** sivá (RAL 7035)  
**Stupeň ochrany:** IP68  
**Trieda horľavosti:** UL94V2  
**Norma:** EN 62444, typ A



CE

Tovar  
na objednávku

TYP	Závit PG a M	Vonkajší priemer kábla (mm)	Rozmery (mm)				Rozmer kľúča (mm)	Balenie (ks)	Číslo produktu
			H	E	L	I			
KDD-9	P9	4,0 - 8,0	23,0	8	45	19	19	1	3.0094510
KDD-11	P11	5,0 - 10,0	27,0	8	50	22	22	1	3.0094550
KDD-13	P13,5	6,0 - 12,0	30,5	9	57	24	24	1	3.0094590
KDD-16	P16	10,0 - 14,0	32,5	10	59	27	27	1	3.0094630
KDD-21	P21	13,0 - 18,0	40,0	11	73	33	33	1	3.0094670
KDD-29	P29	18,0 - 25,0	51,5	11	91	42	42	1	3.0094710
KDD-16M	M16x1,5	4,0 - 8,0	23,0	8	45	19	19	1	3.0095010
KDD-20M	M20x1,5	6,0 - 12,0	30,5	9	57	24	24	1	3.0095020
KDD-25M	M25x1,5	13,0 - 18,0	40,0	11	73	33	33	1	3.0095030
KDD-32M	M32x1,5	18,0 - 25,0	51,5	11	91	42	42	1	3.0095040

Rohový výstup sa dodáva bez matice (N). Súčasťou rohového výstupu je káblová vývodka.

