

OCHRANA KÁBLOV

DW...R - vývodky PG a M

Materiál: telo: PA6.6; tesnenie s membránou: PVC
Pracovná teplota: od -5°C do +70°C
Farba: sivá (RAL 7035)
Stupeň ochrany: IP66
Trieda horľavosti: UL94V2
Norma: EN 62444, typ A



TYP	Závit PG / M	Vonkajší priemer kábla (mm)	Rozmery (mm)		Rozmer kľúča (mm)	Balenie (ks)	Číslo produktu
			L	E	A		
DW-7R	P7	3,0 - 6,0	18	9	15	10	3.0031000
DW-9R	P9	4,0 - 8,0	22	9	19	10	3.0031005
DW-11R	P11	5,0 - 10,0	22	9	22	10	3.0031010
DW-13R	P13,5	7,5 - 13,0	23	10	24	10	3.0031015
DW-16R	P16	9,5 - 15,0	23	10	28	10	3.0031020
DW-21R	P21	13,0 - 19,0	29	11	32	10	3.0031025
DW-29R	P29	15,0 - 25,0	29	12	41	10	3.0031030
DW-36R	P36	21,0 - 32,0	35	14	52	10	3.0031035
DW-42R	P42	26,0 - 38,0	40	16	59	1	3.0031040
DW-48R	P48	31,0 - 44,0	42	18	65	1	3.0031045
DW-12RM	M12x1,5	3,0 - 6,0	18	8	15	10	3.0031050
DW-16RM	M16x1,5	4,0 - 8,0	22	8	19	10	3.0031055
DW-20RM	M20x1,5	7,5 - 13,0	23	9	24	10	3.0031060
DW-25RM	M25x1,5	13,0 - 19,0	29	11	32	10	3.0031065
DW-32RM	M32x1,5	15,0 - 25,0	29	11	41	10	3.0031070
DW-40RM	M40x1,5	21,0 - 32,0	35	13	52	10	3.0031075
DW-50RM	M50x1,6	26,0 - 38,0	40	13	59	1	3.0031080
DW-63RM	M63x1,7	31,0 - 44,0	42	14	65	1	3.0031085

Vývodka sa dodáva bez matice (N) a tesnenia (UUPE).

