

# OCHRANA KÁBLOV

## DP...H - vývodky PG

**Materiál:** telo: PA6  
**Pracovná teplota:** od -30°C do +80°C  
**Farba:** sivá (RAL 7035); čierna BK (RAL 90025)  
**Stupeň ochrany:** IP68  
**Trieda horľavosti:** UL94V2  
**Norma:** EN 62444, typ A



TYP	Závit PG	Vonkajší priemer kábla (mm)	Rozmery (mm)		Rozmer kľúča (mm)			Balenie (ks)	Číslo produktu
			L	E	A	B	C		
DP-7H	P7	3,5 - 6,0	20	8	16	16	18	10	3.0032090
DP-9H	P9	4,5 - 7,0	22	8	19	19	21	10	3.0032120
DP-11H	P11	5,5 - 10,0	24	8	22	22	24	10	3.0032150
DP-13H	P13,5	8,0 - 12,0	27	9	24	24	27	10	3.0032180
DP-16H	P16	10,0 - 14,0	28	10	26	27	29	10	3.0032210
DP-21H	P21	14,0 - 18,0	30	10	32	33	36	10	3.0032240
DP-29H	P29	18,0 - 25,0	38	15	42	42	45	10	3.0032270
DP-36H	P36	24,0 - 32,0	45	18	53	51	57	10	3.0032300
DP-42H	P42	30,0 - 38,0	48	18	61	60	65	1	3.0032330
DP-48H	P48	38,0 - 44,0	48	18	65	64	70	1	3.0032360
DP-63H	70,5 mont. otvor	42,0 - 52,0	58	26	76	76	81	1	3.0032365
DP-7H/BK	P7	3,5 - 6,0	20	8	16	16	18	10	3.0032091
DP-9H/BK	P9	4,5 - 7,0	22	8	19	19	21	10	3.0032121
DP-11H/BK	P11	5,5 - 10,0	24	8	22	22	24	10	3.0032151
DP-13H/BK	P13,5	8,0 - 12,0	27	9	24	24	27	10	3.0032181
DP-16H/BK	P16	10,0 - 14,0	28	10	26	27	29	10	3.0032211
DP-21H/BK	P21	14,0 - 18,0	30	10	32	33	36	10	3.0032241
DP-29H/BK	P29	18,0 - 25,0	38	12	42	42	45	10	3.0032271
DP-36H/BK	P36	24,0 - 32,0	45	14	53	51	57	10	3.0032301
DP-42H/BK	P42	30,0 - 38,0	48	14	61	60	65	1	3.0032331
DP-48H/BK	P48	38,0 - 44,0	48	18	65	64	70	1	3.0032361
DP-63H/BK	70,5 mont. otvor	42,0 - 52,0	58	26	76	76	81	1	3.0032366

Vývodka sa dodáva s maticou (N) a tesneným (UUPE).

